



GRINDING

SOLUTIONS

STRAIGHT-LINE **EDGING MACHINES**

AL M SERIES

TL SERIES

TLR SERIES

TLS SERIES

STRAIGHT-LINE **BEVELLING MACHINES**

GAMMA SERIES



THE WIDEST LINE AVAILABLE IN THE MARKET

GRINDING SOLUTIONS

- > STRAIGHT-LINE EDGING MACHINES
- > STRAIGHT-LINE BEVELLING MACHINES



As our core-business since our foundation, the Lattuada's offering includes more than 40 models of **straight-line edging machines, double-edgers** - which come in several different configurations - **and straight-line bevelling machines** suitable to meet any production need.



performing

**high loading capacity,
jumbo thicknesses**

Our machines can carry sheets weighing up to 1,500 Kg and machine thicknesses measuring up to 100 mm.



productive

smart technology

Automation is an ever-important factor: combining the need for providing high-quality products, without jeopardising flexibility while increasing productivity and cutting costs all at once.



reliable

low maintenance required

We commit towards achieving excellence by making precise choices: saying no to makeshift solutions. We have set up an internal and external supply chain that ensures the highest standards of reliability.



flexible

customised configurations

Our machines are custom-made, to give you more. Consisting of an excellent base structure, they can be configured to meet your needs.



smart

simplicity of use

Easily accessible sophisticated technology: this is our approach when it comes to building machines.



excellent

top performance

Thanks to our know-how developed and perfected in 40 years of research and activity in grinding, we - at Lattuada - design and manufacture machines that guarantee maximum processing end quality.




STRAIGHT-LINE EDGING MACHINES


TECHNICAL DETAILS

Our strength, ever.

A variety of solutions that take the form of a wide range of machines: **more than 40 models that can be specifically configured to ensure maximum productivity.**



- 1-2 **Conveyor** with support **pads**.
- 3-4 Automatic **lubrication system**.
- 5-6 **Lattuada spindles**: a unique solution for the motion transmission.
- 7-8 **Copper pipes for cooling the wheels** and the internal of the spindle tank.
- 9-10 **Electrical system** with supreme quality components, compliant with the **UL/CSA standards** too. **IE3 high efficiency motors**.
- 11 **Digital ammeters** with an automatic polishing wheels wear detection system.



AL M SERIES

RECOMMENDED EVEN FOR LARGE-SCALE PRODUCTION OF MEDIUM THICKNESS SHEETS

Having been conceived and manufactured using some of the technological solutions adopted for the larger series of edging machines, such as the assembly of the same spindles, AL M edging machines can handle high production levels.


These details contribute towards increasing their useful life, while simultaneously reducing the required maintenance.



3 - 20/25 mm
1/8 - 3/4 / 1 "



2000 mm
78.7 "



2400 - 3000 mm
94.5 - 118.1 "



400 Kg - 200 Kg/m
881 lbs - 11.2 lbs/ "



700 Kg
1,543 lbs



AL M SERIES

Electronic straight-line edging machines for processing the **flat edge with arris**



AL T SERIES

Peripheral straight-line edging machines for processing the **pencil edge, OG or flat edge with arris**



AL M SERIES

Electronic straight-line edging machines
for processing the **flat edge with arris**

AL 6 M	eu	0,5 - 4 m/min	H60 mm opt. H35 mm	3 - 20 mm	12,5	5.755x1.450 xH2.400 mm	400 Kg - 200 Kg/m	700 Kg						
	us	20 - 157 "/min	H2.4 " opt. H1.4 "	1/8 - 3/4 "		226.5x57 xH94.5 "	881 lbs - 11.2 lbs/"	1,543 lbs						
AL 7 M	eu	0,5 - 4 m/min	H60 mm opt. H35 mm	3 - 25 mm	15	6.285x1.450 xH3.000 mm	400 Kg -200 Kg/m	700 Kg						
	us	20 - 157 "/min	H2.4 " opt. 1.4 "	1/8 - 1 "		247.4x57 xH118.1 "	881 lbs - 11.2 lbs/"	1,543 lbs						
AL 8 M	eu	0,5 - 4 m/min	H60 mm opt. H35 mm	3 - 25 mm	15	6.285x1.450 xH3.000 mm	400 Kg -200 Kg/m	700 Kg						
	us	20 - 157 "/min	H2.4 " opt. H1.4 "	1/8 - 1 "		247.4x57 xH118.1 "	881 lbs - 11.2 lbs/"	1,543 lbs						
AL 9 M	eu	0,5 - 4 m/min	H60 mm opt. H35 mm	3 - 25 mm	17	6.285x1.450 xH3.000 mm	400 Kg -200 Kg/m	700 Kg						
	us	20 - 157 "/min	H2.4 " opt. H1.4 "	1/8 - 1 "		247.4x57 xH118.1 "	881 lbs - 11.2 lbs/"	1,543 lbs						

LEGEND



speed



minimum glass
size



miter
inclination



workable glass
thickness



installed
power



dimensions



max glass load
(on the conveyor)




max glass
load (total)



dubbing
device

ALT SERIES

Peripheral straight-line edging machines for processing the **pencil edge, OG or flat edge with arris**



AL 4 T	eu	0,5 - 4 m/min	H60 mm	3 - 20 mm	10	6.285x1.450 xH2.400 mm	400 Kg -200 Kg/m	700 Kg		
	us	20 - 157 "/min	H2.4 "	1/8 - 3/4 "		247.4x57 xH94.5 "	881 lbs - 11.2 lbs/"	1,543 lbs		
								4	3	2
										

AL 6 T	eu	0,5 - 4 m/min	H60 mm	3 - 20 mm	12,5	6.285x1.450 xH2.400 mm	400 Kg -200 Kg/m	700 Kg			
	us	20 - 157 "/min	H2.4 "	1/8 - 3/4 "		247.4x57 xH94.5 "	881 lbs - 11.2 lbs/"	1,543 lbs			
							6	5	4	3	2
											



diamond
peripheral wheel



peripheral
polishing wheel



diamond cup
wheel



resin cup
wheel



polishing cup
wheel



cerium impregnated
cup wheel



felt cup
wheel



polishing arris
wheel



diamond arris
wheel



felt arris
wheel

T SERIES

**RECOMMENDED FOR LARGE SCALE
PRODUCTION OF TEMPERED GLASS
AND/OR HIGH-QUALITY FURNISHING GLASS**


Thanks to the reinforced guides and higher pads, TL edging machines can bear greater weight as compared to the previous series. This makes them particularly flexible, given that they can process from glass sheets featuring major thicknesses to small glass strips, up to a minimum of 35 mm in height.



3 - 40 mm
1/8 / 1.5 "



2600 mm
102.4 "



3100 mm
122 "



800 Kg - 250 Kg/m
1,763 lbs - 14 lbs/ "



1,600 Kg
3,527 lbs



TL SERIES

Electronic straight-line edging machines
for processing the **flat edge with arris**



TL AV SERIES

Electronic straight-line edging machine
with **variable angle between 0 and 45°**



TL SERIES

Electronic straight-line edging machines
for processing the **flat edge with arris**

								
TL 10 PC	eu	0,3 - 5 m/min	H60 mm opt. H35 mm	3 - 40 mm opt. 3 - 50 mm	20	7.920x1.600 xH3.120 mm	800 Kg - 250 Kg/m	1.600 Kg
	us	12 - 197 "/min	H2.4 " opt. 1.4 "	1/8 - 1.5 " opt. 1/8 - 2 "		311x62.2 xH122.8 "	1,763 lbs - 14 lbs/'	3,527 lbs
	3* OPTIONAL 		10 9 8 7 6 5 4 3* 2 1					

TL 10 C PC	eu	0,3 - 5 m/min	H60 mm opt. H35 mm	3 - 40 mm opt. 3 - 50 mm	21	7.920x1.600 xH3.120 mm	800 Kg - 250 Kg/m	1.600 Kg
	us	12 - 197 "/min	H2.4 " opt. 1.4 "	1/8 - 1.5 " opt. 1/8 - 2 "		311x62.2 xH122.8 "	1,763 lbs - 14 lbs/''	3,527 lbs
	3* OPTIONAL 		10 9 8 7 6 5 4 3* 2 1 					

TL 11 PC	eu	0,3 - 5 m/min	H60 mm opt. H35 mm	3 - 40 mm opt. 3 - 50 mm	22	7.920x1.600 xH3.120 mm	800 Kg - 250 Kg/m	1.600 Kg
	us	12 - 197 "/min	H2.4 " opt. 1.4 "	1/8 - 1.5 " opt. 1/8 - 2 "		311x62.2 xH122.8 "	1,763 lbs - 14 lbs/”	3,527 lbs
	11 10 9 8 7 6 5 4 3 2 1							



LEGEND



speed



minimum glass
size



miter
inclination



workable glass
thickness



installed
power



dimensions



max glass load
(on the conveyor)



max glass
load (total)



dubbing
device

TL AV SERIES

Electronic straight-line edging machine
with **variable angle between 0 and 45°**

									
TL 9 AV PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45° opt. 0 - 60°	3 - 40 mm opt. 3 - 50 mm	21	7.920x1.600 xH3.120 mm	800 Kg - 250 Kg/m	1.600 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "		1/8 - 1.5 " opt. 1/8 - 2 "		311x62.2 xH122.8 "	1,763 lbs - 14 lbs/'	3,527 lbs
987654321 									

TL 10 AV PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45° opt. 0 - 60°	3 - 40 mm opt. 3 - 50 mm	23	8.210x1.600 xH3.120 mm	800 Kg - 250 Kg/m	1.600 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "		1/8 - 1.5 " opt. 1/8 - 2 "		332.2x62.2 xH122 "	1,763 lbs - 14 lbs/'	3,527 lbs
	3* OPTIONAL  19  9  8  7  6  5  4  3*  2 1								



TJR SERIES

THE MOST WIDELY USED BY
MAJOR GROUPS OF NORTHERN
EUROPE AND USA

Designed for glassmakers handling major volumes
of large sheets and high thicknesses for heavy duty
construction, or for supreme quality works at high speed.



3 - 50 / 55 mm
1/8 - 2 / 2.2 "



2.600 mm / 3.000 mm
102.3 / 118.1 "



3.100 mm / 3.700 mm
122 / 145.6 "



1.100 Kg - 350 Kg/m
2,425 lbs - 19.6 lbs/ "



2.000 Kg
4,409 lbs




TLR SERIES

Electronic straight-line edging machines
for processing the **flat edge with arris**



TLR AV SERIES

Electronic straight-line edging machine
with **variable angle between 0 and 45°**



TLR SERIES

Electronic straight-line edging machines
for processing the **flat edge with arris**

TLR 11 PC	eu	0,3 - 5 m/min	H60 mm opt. H35 mm	3 - 50 mm	22	8.210x1.1600 xH3.120 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H2.4 " opt. 1.4 "	1/8 - 2 "		323.2x62.2 xH122.8 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	3* OPTIONAL		11 10 9 8 7 6 5 4 3* 2 1					

TLR 11 C PC	eu	0,3 - 5 m/min	H60 mm opt. H35 mm	3 - 50 mm	22	8.510x1.600 xH3.120 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H2.4 " opt. 1.4 "	1/8 - 2 "		335x62.2 xH122.8 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	3* OPTIONAL 		11 10 9 8 7 6 5 4 3* 2 1 					

TLR 11 DD PC	eu	0,3 - 5 m/min*	H60 mm	3 - 50 mm**	22	8.510x1.600 xH3.120 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min*	H2.4 "	1/8 - 2 ***		335x62.2 xH122.8 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	3*  OPTIONAL		* max 3,5 m/min (max 137 "/min) (with dubbing device) ** max 15 mm (max 0.6 ") (with dubbing device)		12 11 10 9 8 7 6 5 4 3* 2 1			

TLR 12 C PC	eu	0,3 - 5 m/min	H60 mm opt. H35 mm	3 - 50 mm	23	8.510x1.600 xH3.120 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H2.4 " opt. 1.4 "	1/8 - 2 "		335x62.2 xH122.8 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	12 11 10 9 8 7 6 5 4 3 2 1							

TLR 12 DD PC	eu	0,3 - 5 m/min*	H60 mm	3 - 50 mm**	22	8.970x1.600 xH3.120 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min*	H2.4 "	1/8 - 2 ***		353.1x62.2 xH122.8 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	13 12 11 10 9 8 7 6 5 4 3 2 1		* max 3,5 m/min (max 137 "/min) (with dubbing device) ** max 15 mm (max 0.6 ") (with dubbing device)					

LEGEND



speed



minimum glass
size



miter
inclination



workable glass
thickness



installed
power



dimensions



max glass load
(on the conveyor)



max glass
load (total)



dubbing
device

Electronic straight-line edging machines for processing the **flat edge with arris**



TLR 14 C PC	eu	0,3 - 5 m/min	H60 mm opt. H35 mm	3 - 55 mm	30	9.590x1.700 xH3.700 mm		1.100 Kg - 350 Kg/m		2.000 Kg	
	us	12 - 197 "/min	H2.4 " opt. 1.4 "	1/8 - 2.2 "		377.5x66.9 xH145.6 "		2,425 lbs - 19.6 lbs/"		4,409 lbs	
	14 13 12 11 10 9 8 7 6 5 4 3 2 1										



felt arris
wheel

TLR AV SERIES

Electronic straight-line edging machine
with **variable angle between 0 and 45°**

TLR 10 AV C PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45° opt. 0 - 60°	3 - 50 mm	23	8.510x1.600 xH3.100 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "				335x62.2 xH122 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	10987654321								
TLR 11 AV PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45° opt. 0 - 60°	3 - 50 mm	23	8.510x1.600 xH3.120 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "				335x62.2 xH122.8 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	1110987654321								
TLR 11 AV C PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45° opt. 0 - 60°	3 - 50 mm	23	8.510x1.600 xH3.120 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "				335x62.2 xH122.8 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	1110987654321								
TLR11 AV C DD PC	eu	0,3 - 5 m/min*	H85 mm	0 - 45°	3-50 mm**	25	8.970x1.600 xH3.100 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min*	H3.3 "		1/8 - 2 "***		353.1x62.2 xH122 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
			* max 3,5 m/min (max 137 "/min) (with dubbing device) ** max 15 mm (max 0.6 ") (with dubbing device)		121110987654321				

LEGEND

								
speed	minimum glass size	miter inclination	workable glass thickness	installed power	dimensions	max glass load (on the conveyor)	max glass load (total)	dubbing device

TLR AV SERIES

Electronic straight-line edging machine
with **variable angle between 0 and 45°**




TLR 13 AV C PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45°	3-55 mm	28	9.590x1.700 xH3.700 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "		1/8 - 2.2 "		377.6x66.9 xH145.6 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
13121110987654321 									

TLR 13 AV C DD PC	eu	0,3 - 5 m/min*	H85 mm opt. H60 mm	0 - 45°	3 - 55 mm**	30	10.020x1.600 xH3.700 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min*	H3.3 " opt. H2.4 "		1/8 - 2.2 "***		394.5x62.2 xH145.6 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	* max 3,5 m/min (max 137 "/min) (with dubbing device) ** max 15 mm (max 0.6 ") (with dubbing device)				14 13 12 11 10 9 8 7 6 5 4 3 2 1				

TLR 14 AV C PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45°	3 - 55 mm	30	10.040x1.700 xH3.700 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "		1/8 - 2.2 "		377.6x66.9 xH145.6 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	14  13  12  11  10  9  8  7  6  5  4  3  2  1 								

TLR 16 AV C PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45°	3 - 55 mm	34	10.390x1.700 xH3.700 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "		1/8 - 2.2 "		409x66.9 xH145.6 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 </								



TLS SERIES

THE EVOLUTION OF OUR FAMILY OF TLR EDGING MACHINES

Thanks to some structural changes, mainly due to the application of new pads and reinforced guides, the models of this series are capable of carrying sheets weighing up to 1,500 Kg (on the conveyor) and processing sheets with thickness up to 100 mm.



3 - 60 / 80 / 100 mm
1/8 - 2.4 / 3.1 / 3.9 "



3.000 mm
118.1 "



3.700 mm
145.6 "



1.100 Kg - 350 Kg/m
2,425 lbs - 19.6 lbs/ "



2.200 Kg
4,850 lbs



TLS AV SERIES


Electronic straight-line edging machine
with **variable angle between 0 and 45°**





**THE BIGGEST
EDGING MACHINE
EVER BUILT!**

       									
sp60/80/100	eu	0,3 - 5 m/min	H85 mm	0 - 45°	3 - 60/80/100 mm	32	10.390x1.750 xH3.700 mm	1.100 Kg - 350 Kg/m opt. 1.500 Kg - 350 Kg/m	2.200 Kg
	us	12 - 197 "/min	H3.3 "		1/8 - 2.4/3.1/3.9 "		409x68.9 xH145.6 "	2.425 lbs - 19.6 lbs/" opt. 3.307 lbs - 19.6 lbs/"	4,850 lbs
	15 14 13 12 11 10 9 8 7 6 5 4 3 2 1								





ACCESSORIES

STRAIGHT-LINE EDGING MACHINES

The washing machine applied to the edging machines and bevelling machines outlet conveyor allows the complete cleaning and drying of the processed edges of the glass sheets.



OT 300	eu	300x300 mm	the same of the machine on which it is fitted on	2 *	550x600 xH770 mm	2
	us	11.8x11.8 "			21.6x23.6 xH30.3 "	
				*standard (t may change according to the included options)		

PAR-AL: device for processing parallelogram-shaped glasses.



LOOK AT THE DEVICE AT WORK





PANEL

TOUCH SCREEN OPERATOR

The **only one in the market** capable of guaranteeing constant monitoring of the various functions of the machine through different control methods.

BASIC 4 "

Machine's data and maintenance information panel



ADVANCED 10 "

Panel for the control and management of all work steps



ADVANCED 12 "

Panel for the control and management of all work steps for automatic machines (with A-WR and i-AL packages)



STRAIGHT-LINE BEVELLING MACHINES

TECHNICAL DETAILS

Bevelling has always considered the **most complex edging operation**.

This is why Lattuada manufactures very precise and accurate bevelling machines, renowned for their reliability, low maintenance and duration over time.



- 1 **Numerous wheel configurations** available, even customised.
- 2 **Quick and simple** wheel change.
- 3 Managing all work steps through a **touch screen operator panel**.
- 4 **Small piece processing** system.
- 5 OT 300 **washing machine**.
- 6 Motor absorption **digital ammeters**.
- 7 Pads washing **rotary brush**.
- 8 **Automatic** lubrication.
- 9 Variation of the conveyor speed by **means of the inverter**.
- 10 Version with 4 felts: **high processing speed and quality!**



GAMMA

SERIES

THE WIDEST RANGE CURRENTLY AVAILABLE IN THE MARKET, IT OFFERS TECHNICAL SOLUTIONS CAPABLE OF MEETING ANY PRODUCTION NEED

GAMMA 8, which combines the versatility of a small machine with the capacity of processing on sizeable productions, even thanks to the three felts it is provided with, we go all the way to the “elder sisters”: recommended for glassmakers in need of machines capable of operating at high speeds and with utmost quality level.



3 - 20 / 25 mm
1/8 - 3/4 / 1"



2.000 / 2.600 mm
78.7 / 102.3"



2.450 / 3.100 mm
96.5 / 122"



500 Kg - 150 Kg/m
1,102 lbs - 8.4 lbs/"



mechanical



GAMMA SERIES

Straight-line bevelling machines
for processing **the bevel** and **flat edge with arris**,
using **liquid cerium oxide**



GAMMA SERIES

Straight-line bevelling machines for processing
the **polished bevel** using **liquid cerium oxide**

				STANDARD	OPTIONAL			Kw.		
GAMMA 8 PC	eu	0,5 - 4 m/min	110x110 mm opt. 40x40 mm	3 - 45°	3 - 25°	40 mm	3 - 20 mm	18	6.510x1.350 xH2.450 mm	500 Kg - 150 Kg/m
	us	20 - 157 "/min	4.3x4.3 " opt. 1.6x1.6 "			1.6 "	1/8 - 3/4 "		256.2x53.1 xH96.5 "	1,102 lbs - 8.4 lbs/m
		3* OPTIONAL								
GAMMA 613 PC	eu	0,3 - 5 m/min	110x110 mm opt. 40x40 mm	3 - 45°	3 - 25°	50 mm	3 - 25 mm	23	8.420x1.600 xH3.100 mm	500 Kg - 150 Kg/m
	us	12 - 197 "/min	4.3x4.3 " opt. 1.6x1.6 "			2 "	1/8 - 1 "		331.4x62.2 xH123.2 "	1,102 lbs - 8.4 lbs/m
		4* OPTIONAL								
GAMMA 614 PC	eu	0,3 - 5 m/min	110x110 mm opt. 40x40 mm	3 - 45°	3 - 25°	50 mm	3 - 25 mm	26	8.420x1.600 xH3.100 mm	500 Kg - 150 Kg/m
	us	12 - 197 "/min	4.3x4.3 " opt. 1.6x1.6 "			2 "	1/8 - 1 "		331.4x62.2 xH123.2 "	1,102 lbs - 8.4 lbs/m
		4* OPTIONAL								
GAMMA 713 PC	eu	0,3 - 5 m/min	110x110 mm opt. 40x40 mm	3 - 45°	3 - 25°	50 mm	3 - 25 mm	26	8.420x1.600 xH3.100 mm	500 Kg - 150 Kg/m
	us	12 - 197 "/min	4.3x4.3 " opt. 1.6x1.6 "			2 "	1/8 - 1 "		331.4x62.2 xH123.2 "	1,102 lbs - 8.4 lbs/m
		4* OPTIONAL								

Straight-line bevelling machines for processing
the **bevel and pencil edge**, using **liquid cerium oxide**

GAMMA 633 PC	eu	0,3 - 5 m/min	110x110 mm opt. 40x40 mm	3 - 45°	3 - 25°	50 mm	3 - 25 mm	27	8.880x1.600 xH3.100 mm	500 Kg - 150 Kg/m
	us	12 - 197 "/min	4.3x4.3 " opt. 1.6x1.6 "			2 "	1/8 - 1 "		349.6x62.2 xH123.2 "	1,102 lbs - 8.4 lbs/m
		7* OPTIONAL								

Straight-line bevelling machines for processing
the **bevel and flat edge with arris**, using **liquid cerium oxide**

GAMMA 643 PC	eu	0,3 - 5 m/min	110x110 mm opt. 40x40 mm	3 - 45°	50 mm	3 - 25 mm	32	8.880x1.600 xH3.100 mm	500 Kg - 150 Kg/m
	us	12 - 197 "/min	4.3x4.3 " opt. 1.6x1.6 "		2 "	1/8 - 1 "		349.6x62.2 xH123.2 "	1,102 lbs - 8.4 lbs/m
									

GAMMA 723 PC	eu	0,3 - 5 m/min	110x110 mm opt. 40x40 mm	3 - 45°	50 mm	3 - 25 mm	32	8.880x1.600 xH3.100 mm	500 Kg - 150 Kg/m
	us	12 - 197 "/min	4.3x4.3 " opt. 1.6x1.6 "		2 "	1/8 - 1 "		349.6x62.2 xH123.2 "	1,102 lbs - 8.4 lbs/m
	OPTIONAL 								



ACCESSORIES

STRAIGHT-LINE BEVELLING MACHINES

The washing machine applied to the edging machines and beveling machines outlet conveyor allows the complete cleaning and drying of the processed edges of the glass sheets.



OT 300						
eu	300x300 mm	the same of the machine on which it is fitted on		2 *	550x600xH770 mm	2
us	11.8x11.8 "				21.6x23.6xH30.3 "	

*standard (it may change according to the included options)

PANEL

TOUCH SCREEN OPERATOR

The **only one in the market** capable of guaranteeing constant monitoring of the various functions of the machine through different control methods.

ADVANCED 10.4 "

Panel for the control and management of all work steps



diamond cup wheel



peripheral polishing wheel



diamond cup wheel



resin cup wheel



polishing cup wheel



felt cup wheel



polishing aris wheel